

Safety Data Sheet

EnerFlex-SB 100



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

EnerFlex SB 100
HS number:32141010

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Waterproofing
Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

ENERCON Specialists LLC
Suite 164, 3853 Northdale Blvd
Tampa, Florida 33624, USA
Phone.: +1 786 726 0788
info@enercon-group.com / www.enercon-group.com

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

This product contains less than 1% respirable crystalline silica, so it does not require classification

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Skin Sens. 1B: Sensitization, skin, Category 1B, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Skin Sens. 1B: H317 - May cause an allergic skin reaction

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P261: Avoid breathing dust/fume/gas/mist/vapours/spray
P272: Contaminated work clothing should not be allowed out of the workplace
P280: Wear protective gloves/protective clothing/eye protection/face protection
P302+P352: IF ON SKIN: Wash with plenty of water
P333+P313: If skin irritation or rash occurs: Get medical advice/attention
P501: Dispose of contents/container according to the separated collection system used in your municipality

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking
Contains 2-butanone oxime, Butan-2-one O,O',O''-(vinylsilylidyne)trioxime, N-(3-(trimethoxysilyl)propyl)ethylenediamine

Substances that contribute to the classification

Butan-2-one O,O',O''-(methylsilylidyne)trioxime

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

3.2 Mixture:

Chemical description: Silicone-based mixed solvent

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 64742-48-9 EC: 918-481-9 Index: Non-applicable REACH: Non-applicable	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics⁽¹⁾ Self-classified Regulation 1272/2008 Asp. Tox. 1: H304; EUH066 - Danger	10 - <25 %
CAS: 22984-54-9 EC: 245-366-4 Index: Non-applicable REACH: 01-2119970560-38-XXXX	Butan-2-one O,O',O''-(methylsilyldiyl)trioxime⁽¹⁾ Self-classified Regulation 1272/2008 Eye Irrit. 2: H319; Skin Sens. 1B: H317; STOT RE 2: H373 - Warning	1 - <2,5 %
CAS: 96-29-7 EC: 202-496-6 Index: 616-014-00-0 REACH: 01-2119539477-28-XXXX	2-butanone oxime⁽¹⁾ ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	<1 %
CAS: 2224-33-1 EC: 218-747-8 Index: Non-applicable REACH: 01-2119970537-27-XXXX	Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime⁽¹⁾ Self-classified Regulation 1272/2008 Eye Dam. 1: H318; Skin Sens. 1B: H317; STOT RE 2: H373 - Danger	<1 %
CAS: 1760-24-3 EC: 217-164-6 Index: Non-applicable REACH: 01-2119970215-39-XXXX	N-(3-(trimethoxysilyl)propyl)ethylenediamine⁽¹⁾ Self-classified Regulation 1272/2008 Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	<1 %
CAS: 74956-86-8 EC: 220-011-6 Index: Non-applicable REACH: 01-2119970892-25-XXXX	[3-(2,3-epoxypropoxy)propyl]triethoxysilane⁽¹⁾ Self-classified Regulation 1272/2008 Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	<1 %
CAS: 77-58-7 EC: 201-039-8 Index: 050-030-00-3 REACH: 01-2119496068-27-XXXX	Dibutyltin Dilaurate⁽¹⁾ Self-classified Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Muta. 2: H341; Repr. 1B: H360; Skin Corr. 1C: H314; Skin Sens. 1: H317; STOT RE 1: H372; STOT SE 1: H370 - Danger	<1 %
CAS: 107-15-3 EC: 203-468-6 Index: 612-006-00-6 REACH: 01-2119480383-37-XXXX	Ethylenediamine⁽¹⁾ ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H302+H312; Flam. Liq. 3: H226; Resp. Sens. 1: H334; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	<1 %
CAS: 67-56-1 EC: 200-659-6 Index: 603-001-00-X REACH: 01-2119433307-44-XXXX	methanol⁽¹⁾ ATP CLP00 Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	<1 %

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 4: FIRST AID MEASURES (continued)

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 7: HANDLING AND STORAGE (continued)

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
 Maximum Temp.: 30 °C
 Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Occupational exposure limits		
	IOELV (8h)	200 ppm	260 mg/m ³
methanol CAS: 67-56-1 EC: 200-659-6	IOELV (STEL)		

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butan-2-one O,O',O''-(methylsilyldi)trioxime CAS: 22984-54-9 EC: 245-366-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,988 mg/m ³	Non-applicable
2-butanone oxime CAS: 96-29-7 EC: 202-496-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	2,5 mg/kg	Non-applicable	1,3 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	9 mg/m ³	3,33 mg/m ³
Butan-2-one O,O',O''-(vinylsilyldi)trioxime CAS: 2224-33-1 EC: 218-747-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1,03 mg/m ³	Non-applicable
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	5 mg/kg	Non-applicable	5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	35,3 mg/m ³	Non-applicable
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	1 mg/kg	Non-applicable	0,2 mg/kg	Non-applicable
	Inhalation	0,07 mg/m ³	Non-applicable	0,01 mg/m ³	Non-applicable
methanol CAS: 67-56-1 EC: 200-659-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	40 mg/kg	Non-applicable	40 mg/kg	Non-applicable
	Inhalation	260 mg/m ³	260 mg/m ³	260 mg/m ³	260 mg/m ³

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-butanone oxime CAS: 96-29-7 EC: 202-496-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	1,5 mg/kg	Non-applicable	0,78 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2,7 mg/m ³	2 mg/m ³
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	Oral	Non-applicable	Non-applicable	2,5 mg/kg	Non-applicable
	Dermal	17 mg/kg	Non-applicable	2,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	8,7 mg/m ³	Non-applicable
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	Oral	0,01 mg/kg	Non-applicable	0,002 mg/kg	Non-applicable
	Dermal	0,5 mg/kg	Non-applicable	0,08 mg/kg	Non-applicable
	Inhalation	0,02 mg/m ³	Non-applicable	0,003 mg/m ³	Non-applicable
methanol CAS: 67-56-1 EC: 200-659-6	Oral	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
	Dermal	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
	Inhalation	50 mg/m ³	50 mg/m ³	50 mg/m ³	50 mg/m ³

PNEC:

Identification				
Butan-2-one O,O',O''-(methylsilylidyne)trioxime CAS: 22984-54-9 EC: 245-366-4	STP	10 mg/L	Fresh water	0,26 mg/L
	Soil	0,05 mg/kg	Marine water	0,026 mg/L
	Intermittent	0,12 mg/L	Sediment (Fresh water)	1,02 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,102 mg/kg
2-butanone oxime CAS: 96-29-7 EC: 202-496-6	STP	177 mg/L	Fresh water	0,256 mg/L
	Soil	Non-applicable	Marine water	Non-applicable
	Intermittent	0,118 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1 EC: 218-747-8	STP	10 mg/L	Fresh water	0,26 mg/L
	Soil	0,05 mg/kg	Marine water	0,026 mg/L
	Intermittent	0,12 mg/L	Sediment (Fresh water)	1,02 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,102 mg/kg
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	STP	25 mg/L	Fresh water	0,062 mg/L
	Soil	0,0085 mg/kg	Marine water	0,0062 mg/L
	Intermittent	0,62 mg/L	Sediment (Fresh water)	0,22 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,022 mg/kg
[3-(2,3-epoxypropoxy)propyl]triethoxysilane CAS: 74956-86-8 EC: 220-011-6	STP	100 mg/L	Fresh water	0,1 mg/L
	Soil	0,24 mg/kg	Marine water	0,01 mg/L
	Intermittent	1 mg/L	Sediment (Fresh water)	1,5 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,15 mg/kg
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	STP	100 mg/L	Fresh water	0,000463 mg/L
	Soil	Non-applicable	Marine water	0,000463 mg/L
	Intermittent	0,00463 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	0,2 g/kg	Sediment (Marine water)	Non-applicable
methanol CAS: 67-56-1 EC: 200-659-6	STP	100 mg/L	Fresh water	154 mg/L
	Soil	23,5 mg/kg	Marine water	15,4 mg/L
	Intermittent	1540 mg/L	Sediment (Fresh water)	570,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



- CONTINUED ON NEXT PAGE -

Safety Data Sheet



EnerFlex-SB 100



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"



D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks		EN 13034:2005+A1:2009 EN 168:2001 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk		EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	21,57 % weight
V.O.C. density at 20 °C:	0,27 kg/m ³ (0,27 g/L)
Average carbon number:	8,78
Average molecular weight:	128,07 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	Not available
Odour:	Not available
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	211 °C
Vapour pressure at 20 °C:	58 Pa
Vapour pressure at 50 °C:	427,91 Pa (0,43 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	1,3 kg/m ³
Relative density at 20 °C:	1,265
Dynamic viscosity at 20 °C:	1800 - 2200 cP
Kinematic viscosity at 20 °C:	1500 cSt
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

Flammability:

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	Non-applicable *
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Explosive:

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

9.2 Other information:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
IARC: Silicon dioxide (RCS < 1%) (3)
- Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous as a result of a single exposure. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	Route	Dose	
Butan-2-one O,O',O''-(methylsilylidyne)trioxime CAS: 22984-54-9 EC: 245-366-4	LD50 oral	2247 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
2-butanone oxime CAS: 96-29-7 EC: 202-496-6	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	Non-applicable	
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1 EC: 218-747-8	LD50 oral	3519 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	LD50 oral	2413 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	LD50 oral	175 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
methanol CAS: 67-56-1 EC: 200-659-6	LD50 oral	100 mg/kg	Rat
	LD50 dermal	300 mg/kg	Rabbit
	LC50 inhalation	3 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	Route	Dose		
2-butanone oxime CAS: 96-29-7 EC: 202-496-6	LC50	843 mg/L (96 h)	Pimephales promelas	Fish
	EC50	750 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	83 mg/L (72 h)	Scenedesmus subspicatus	Algae
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1 EC: 218-747-8	LC50	55000 mg/L (96 h)	QSAR	Fish
	EC50	17168 mg/L (48 h)	QSAR	Fish
	EC50	1429 mg/L (96 h)	QSAR	Fish
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	LC50	597 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	81 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	8.8 mg/L (72 h)	Selenastrum capricornutum	Algae
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	LC50	0.1 - 1 mg/L (96 h)		Fish
	EC50	0.1 - 1 mg/L		Crustacean
	EC50	0.1 - 1 mg/L		Algae
methanol CAS: 67-56-1 EC: 200-659-6	LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	12000 mg/L (96 h)	Nitrocra spinipes	Crustacean
	EC50	530 mg/L (168 h)	Microcystis aeruginosa	Algae

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 12: ECOLOGICAL INFORMATION (continued)

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
2-butanone oxime CAS: 96-29-7 EC: 202-496-6	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	24 %
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime CAS: 2224-33-1 EC: 218-747-8	BOD5	Non-applicable	Concentration	20 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	39 %
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	BOD5	0.00054 g O2/g	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	50 %
methanol CAS: 67-56-1 EC: 200-659-6	BOD5	Non-applicable	Concentration	100 mg/L
	COD	1.42 g O2/g	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	Parameter	Value
2-butanone oxime CAS: 96-29-7 EC: 202-496-6	BCF	5
	Pow Log	0.59
	Potential	Low
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime CAS: 2224-33-1 EC: 218-747-8	BCF	1
	Pow Log	0.6
	Potential	Low
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	BCF	31
	Pow Log	3.12
	Potential	Moderate
methanol CAS: 67-56-1 EC: 200-659-6	BCF	3
	Pow Log	-0.77
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Parameter	Value	Parameter	Value
2-butanone oxime CAS: 96-29-7 EC: 202-496-6	Koc	3	Henry	Non-applicable
	Conclusion	Very High	Dry soil	Non-applicable
	Surface tension	2,57E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethylenediamine CAS: 107-15-3 EC: 203-468-6	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	4,188E-2 N/m (25 °C)	Moist soil	Non-applicable
methanol CAS: 67-56-1 EC: 200-659-6	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,355E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 12	waste paint and varnish other than those mentioned in 08 01 11	Non dangerous

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Ethylenediamine

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Dibutyltin Dilaurate

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

—tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The provider has carried out a chemical safety assessment

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

- CONTINUED ON NEXT PAGE -

Safety Data Sheet

EnerFlex-SB 100



SECTION 16: OTHER INFORMATION (continued)

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed substances
Not a hazardous substance

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin
Acute Tox. 4: H312 - Harmful in contact with skin
Aquatic Acute 1: H400 - Very toxic to aquatic life
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
Carc. 2: H351 - Suspected of causing cancer
Eye Dam. 1: H318 - Causes serious eye damage
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Liq. 2: H225 - Highly flammable liquid and vapour
Flam. Liq. 3: H226 - Flammable liquid and vapour
Muta. 2: H341 - Suspected of causing genetic defects
Repr. 1B: H360 - May damage fertility or the unborn child
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage
Skin Corr. 1C: H314 - Causes severe skin burns and eye damage
Skin Irrit. 2: H315 - Causes skin irritation
Skin Sens. 1: H317 - May cause an allergic skin reaction
Skin Sens. 1B: H317 - May cause an allergic skin reaction
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. (Oral)
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)
STOT SE 1: H370 - Causes damage to organs

Classification procedure:

Skin Sens. 1B: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -